

授权合作伙伴/Authorized Business Partner:

inventronics

Indoor Constant Current LED Drivers - Linear

室内恒流LED驱动电源 - 长条形

本产品仅作市场宣传，如有更改，恕不另行通知。具体参数及规格，请以产品说明书为准。

Contact Us / 联系我们:

E-mail: ds_mktg@inventronicsglobal.com
www.inventronics-light.com
更多信息，请关注微信公众号



V09/2025

inventronics



www.inventronics-light.com



Table with 25 columns: Product Family, Product Name, EAN10, Isolation, Dimming Interface, Dimming Range, Emergency Lighting, Nominal Voltage, Nominal Frequency, Networked Standby Power, Power Factor, THD, Output Power, Output Voltage, Output Current, Ripple, Efficiency, Dimensions, Cable clamp kit, Surge transient protection, IP Rating, Ta, Max Tc, Lifetime, Programmer Tool, Certificates & Approbations. Rows include categories like OTI WI D NFC BL/CA L, OTI WI NFC BL/CA L, OTI DX D NFC L, OTI DALI D NFC TW L, OTI DALI NFC TW L, OTI DALI D NFC IND L, OTI DALI D NFC F L, OTI DALI NFC L, IT DALI D LT2 L, IT DALI LT2 L, LUM Series, OT FIT D NFC IND L, OT FIT D NFC F L, OT FIT D NFC L, OT FIT NFC L, EM FIT CS L, EM FIT D CS L.

备注: 运行在最高Tc温度下的产品寿命, 最大失效率为10% Remark: At Tc max. temperature, max. failure rate of 10 %