

授权合作伙伴/Authorized Business Partner:

inventronics

# Indoor Constant Current LED Drivers - Linear

## 室内恒流LED驱动电源 - 长条形

本产品仅作市场宣传，如有更改，恕不另行通知。具体参数及规格，请以产品说明书为准。

Contact Us / 联系我们:

E-mail: [ds\\_mktg@inventronicsglobal.com](mailto:ds_mktg@inventronicsglobal.com)  
[www.inventronics-light.com](http://www.inventronics-light.com)  
更多信息，请关注微信公众号



V09/2025

inventronics



[www.inventronics-light.com](http://www.inventronics-light.com)



Product Family 系列	Product Name 产品名称	EAN10 订货号	Isolation 隔离	Dimming Interface 调光方式	Dimming Range 调光区间	Emergency Lighting 应急照明	Normal Voltage 额定电压 [V]	Normal Frequency 工作频率 [Hz]	Networked Standby Power 待机功率 [W]	Power Factor (@full load) 功率因数 (满载)	THD (@full load) 总谐波 [V]	Output Power 输出功率 [W]	Output Voltage 输出电压 [V]	Output Current 输出电流 [mA]	Ripple (100Hz) 纹波电流 [%]	Efficiency (max.) 最大效率 [%]	Dimensions 外形尺寸 (LxWxH) [mm]	Cable clamp kit 压线夹	Surge transient protection 浪涌保护 [kV]	IP Rating 防护等级	Ta 工作环境温度 [°C]	Max Tc 最高温度 [°C]	Lifetime 产品寿命 @tc max	Programmer Tool 编程工具	Certificates & Approbations 认证
OT WI D NFC BL/CA L	OT WI 35/220-240/400 D NFC CA L	693718611999	Non-isolated	Casambi	1 - 100%	Yes	220-240	0 / 50 / 60	<0.15	>0.97	<10 %	4 - 38	54 - 240	75 - 400	<1	93	280 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer	CE/ENEC/CB/RCM/CCC/BIS/KC
	OT WI 75/220-240/550 D NFC CA L	6937186112026	Non-isolated	Casambi	1 - 100%	Yes	220-240	0 / 50 / 60	<0.25	>0.95	<10 %	6.5 - 75	54 - 240	125 - 550	<1	93	280 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer	CE/ENEC/CB/RCM/CCC/BIS/KC
	OT WI 100/220-240/750 D NFC CA L	6937186112033	Non-isolated	Casambi	1 - 100%	Yes	220-240	0 / 50 / 60	<0.25	>0.95	<10 %	5.4 - 100	54 - 240	100 - 750	<1	94	280 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer	CE/ENEC/CB/RCM/CCC/BIS/KC
	OT WI 35/220-240/400 D NFC BL L	6937186112057	Non-isolated	HubSense	1 - 100%	Yes	220-240	0 / 50 / 60	<0.15	>0.97	<10 %	4 - 38	54 - 240	75 - 400	<1	92	280 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer	CE/ENEC/CB/RCM/CCC/BIS/KC
	OT WI 75/220-240/550 D NFC BL L	6937186112071	Non-isolated	HubSense	1 - 100%	Yes	220-240	0 / 50 / 60	<0.25	>0.95	<10 %	6.5 - 75	54 - 240	125 - 550	<1	93	280 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer	CE/ENEC/CB/RCM/CCC/BIS/KC
OT WI NFC BL/CA L	OT WI 100/220-240/750 D NFC BL L	6937186112095	Non-isolated	HubSense	1 - 100%	Yes	220-240	0 / 50 / 60	<0.25	>0.95	<10 %	5.4 - 100	54 - 240	100 - 750	<1	94	280 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer	CE/ENEC/CB/RCM/CCC/BIS/KC
	OT WI 35/220-240/1A0 NFC CA L	6937186112118	SELV	CASAMBI	1 - 100%	Yes	220-240	0 / 50 / 60	<0.2	>0.95	<10 %	4 - 37	15 - 54	200 - 1050	<3	89	280 x 30 x 21	N/A	1   2	IP20	-25...+60	80	50,000	NFC Programmer	CE/ENEC/CB/RCM/CCC/BIS/KC
	OT WI 50/220-240/1A4 NFC CA L	6937186112132	SELV	CASAMBI	1 - 100%	Yes	220-240	0 / 50 / 60	<0.2	>0.95	<10 %	15 - 54	15 - 54	400 - 1400	<3	90	280 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer	CE/ENEC/CB/RCM/CCC/BIS/KC
	OT WI 80/220-240/2A1 NFC CA L	6937186112156	SELV	CASAMBI	1 - 100%	Yes	220-240	0 / 50 / 60	<0.2	>0.95	<10 %	32 - 80	20 - 54	600 - 2100	<3	90	280 x 30 x 21	N/A	1   2	IP20	-25...+60	80	50,000	NFC Programmer	CE/ENEC/CB/RCM/CCC/BIS/KC
	OT WI 220-240/1A0 NFC BL L	6937186112170	SELV	HubSense	1 - 100%	Yes	220-240	0 / 50 / 60	<0.2	>0.95	<10 %	4 - 37	15 - 54	200 - 1050	<3	89	280 x 30 x 21	N/A	1   2	IP20	-25...+60	80	50,000	NFC Programmer	CE/ENEC/CB/RCM/CCC/BIS/KC
OTI DX D NFC L	OTI WI 50/220-240/1A4 NFC BL L	6937186112194	SELV	HubSense	1 - 100%	Yes	220-240	0 / 50 / 60	<0.2	>0.95	<10 %	15 - 54	15 - 54	400 - 1400	<3	90	280 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer	CE/ENEC/CB/RCM/CCC/BIS/KC
	OTI WI 80/220-240/2A1 NFC BL L	6937186112217	SELV	HubSense	1 - 100%	Yes	220-240	0 / 50 / 60	<0.2	>0.95	<10 %	32 - 80	20 - 54	600 - 2100	<3	90	280 x 30 x 21	N/A	1   2	IP20	-25...+60	80	50,000	NFC Programmer	CE/ENEC/CB/RCM/CCC/BIS/KC
	OTI DX 35/220...240/400 D NFC L	6937186111852	Non-isolated	DEXAL(D4)	0.1 - 100%	Yes	220-240	0 / 50 / 60	<0.25	>0.95	<10 %	4-38	54 - 240	75 - 400	<4	90	360 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
	OTI DX 75/220...240/600 D NFC L	6937186111876	Non-isolated	DEXAL(D4)	0.1 - 100%	Yes	220-240	0 / 50 / 60	<0.25	>0.95	<10 %	6.75-75	54 - 240	120 - 600	<4	93	360 x 30 x 21	N/A	1   2	IP20	-25...+65	75	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
	OTI DX 100/220...240/700 D NFC IND L	6937186111890	Non-isolated	DEXAL(D4)	1 - 100%	Yes	220-240	0 / 50 / 60	<0.25	>0.95	<10 %	23-100	64 - 300	200 - 700	<1	93	425 x 30 x 21	N/A	1   2	IP20	-40...+70	85	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
OTI DALI D NFC TW L	OTI DX 150/220...240/850 D NFC IND L	6937186111920	Non-isolated	DEXAL(D4)	1 - 100%	Yes	220-240	0 / 50 / 60	<0.25	>0.95	<10 %	43-150	64 - 300	250 - 850	<1	93	425 x 30 x 21	N/A	1   2	IP20	-40...+65	85	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
	OTI DALI 35/220...240/400 D NFC TW L	6937186112231	Non-isolated	DALI-2 (incl. -251, -252, -253)/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.2	>0.95	<10 %	4 - 38	45 - 240	75 - 400	<1	90	360 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
	OTI DALI 75/220...240/700 D NFC TW L	6937186112255	Non-isolated	DALI-2 (incl. -251, -252, -253)/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.2	>0.95	<10 %	8.1 - 75	50 - 240	150 - 700	<1	91	360 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
	OTI DALI 150/220...240/1A6 D NFC TW L	6937186112316	SELV	DALI-2 (incl. -251, -252, -253)/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.2	>0.95	<10 %	4 - 38	15 - 54	200 - 700	<1	88	360 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
	OTI DALI 75/220-240/1A4 NFC TW L	6937186112330	SELV	DALI-2 (incl. -251, -252, -253)/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.2	>0.95	<10 %	8 - 75	15 - 54	400 - 1400	<1	90	360 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
OTI DALI D NFC IND L	OTI DALI 75/220-240/550 D NFC IND L	6977770436589	Non-isolated	DALI-2 (incl. -251, -252, -253)/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.2	>0.98	<10 %	8 - 75	64 - 300	125 - 550	<1	94	360 x 30 x 21	N/A	4   4	IP20	-40...+70	85	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
	OTI DALI 100/220...240/700 D NFC IND L	6977770436503	Non-isolated	DALI-2 (incl. -251, -252, -253)/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.2	>0.98	<10 %	28 - 100	64 - 300	200 - 700	<1	95	360 x 30 x 21	N/A	4   4	IP20	-40...+70	85	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
	OTI DALI 150/220-240/700 D NFC IND L	6977770436626	Non-isolated	DALI-2 (incl. -251, -252, -253)/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	≤0.22	>0.98	<10 %	43 - 150	64 - 260	200 - 700	<1	94	360 x 30 x 21	N/A	4   4	IP20	-40...+60	85	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
	OTI DALI 150/220...240/1A6 D NFC IND L	6977770436527	Non-isolated	DALI-2 (incl. -251, -252, -253)/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.2	>0.98	<10 %	43 - 150	64 - 300	250 - 1000	<1	95	425 x 30 x 21	N/A	4   4	IP20	-40...+65	85	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
	OTI DALI 300/220...240/1A6 D NFC IND L	6977770436602	Non-isolated	DALI-2 (incl. -251, -252, -253)/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.2	>0.98	<10 %	80 - 300	60 - 300	250 - 1550	<1	96	360 x 46 x 28	N/A	4   4	IP20	-40...+60	85	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
OTI DALI D NFC F L	OTI DALI 25/220-240/200 D NFC F L	6977770436787	Non-isolated	DALI-2 (incl. -251, -252, -253)/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.15	>0.95	<10 %	2.7 - 25	54 - 240	35 - 300	<1	90.5	280 x 30 x 16	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
	OTI DALI 35/220-240/400 D NFC F L	6977770436749	Non-isolated	DALI-2 (incl. -251, -252, -253)/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.15	>0.97	<10 %	4 - 38	54 - 240	75 - 400	<1	92	280 x 30 x 16	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
	OTI DALI 75/220-240/500 D NFC F L	6977770436763	Non-isolated	DALI-2 (incl. -251, -252, -253)/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.15	>0.98	<10 %	6.5 - 75	54 - 240	120 - 500	<1	94	280 x 30 x 16	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
	OTI DALI 25/220-240/700 NFC L	6937186106582	SELV	DALI-2/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.15	>0.95	<15 %	2 - 28	15 - 54	180 - 700	<3	90	280 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
	OTI DALI 35/220-240/1A0 NFC L	6937186106605	SELV	DALI-2/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.15	>0.99	<10 %	4 - 37	15 - 54	200 - 1050	<3	90	280 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
IT DALI D LT2 L	OTI DALI 50/220-240/1A4 NFC L	6977078993401	SELV	DALI-2/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.15	>0.99	<10 %	12 - 54	15 - 54	400 - 1400	<3	91	280 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
	OTI DALI 80/220...240/2A1 NFC L	6937186106629	SELV	DALI-2/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.15	>0.99	<10 %	32 - 80	20 - 54	600 - 2100	<3	91	360 x 30 x 21	N/A	1   2	IP20	-25...+60	80	50,000	NFC Programmer/DALI MAGIC	CE/ENEC/CB/RCM/CCC/BIS/KC
	IT DALI 40/220-240/450 D LT2 L	6977770436381	Non-isolated	DALI-2/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.25	>0.97	<10 %	5.4 - 40	54 - 240	100 - 450	<4	92	280 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	DALI MAGIC / LT2	CE/ENEC/CB/RCM/CCC/BIS/KC
	IT DALI 75/220-240/550 D LT2 L	6977770436404	Non-isolated	DALI-2/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.25	>0.98	<10 %	18 - 75	90 - 240	200 - 550	<4	94	280 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	DALI MAGIC / LT2	CE/ENEC/CB/RCM/CCC/BIS/KC
	IT DALI 100/220-240/800 D LT2 L	6977770436428	Non-isolated	DALI-2/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.25	>0.98	<10 %	27 - 100	90 - 240	300 - 800	<4	94	280 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	DALI MAGIC / LT2	CE/ENEC/CB/RCM/CCC/BIS/KC
IT DALI LT2 L	IT DALI 25/220-240/500 LT2 L	6977770430471	SELV	DALI-2/Touch DIM/Corridor	1 - 100%	Yes	220-240	0 / 50 / 60	<0.4	>0.99	<10 %	4 - 25	20 - 54	200 - 500	<3	91.6	280 x 30 x 21	N/A	1   2	IP20	-25...+60	75	50,000	DALI MAGIC / LT2	CE/ENEC/CB/RCM/CCC/BIS/KC