

CNV-DAL I2 兼容的驱动器列表:

功率 (W)	驱动器系列	型号 (×10 = mA)	后缀	IP 等级	输入电压范围 (Vac)
30	IT 0-10 30/100-277 P67	0A5/1A05	A12	IP67	90-305
50	IT 0-10 50/100-277 P67	0A53/0A9/1A5	A12	IP67	90-305
75	IT 0-10 75/100-277 P67	0A53/1A05/2A1	A12	IP67	90-305
75	EUD-075S	070/105/175/180/280	DT/DV	IP67	90-305
96	EUD-096S	070/105/210/215/350	DVA/DTA	IP67	90-305
100	EUM-100S	105/150/280	MG/MT	IP66/IP67	90-305
100	IT 0-10 100/100-277/N E A12	0A5	A12 OP	IP20	90-305
100	IT 0-10 100/100-277/N F A12	0A5	A12 OP	IP20	90-305
100	IT 0-10 100/100-277 P67	0A53/1A05/2A8	A12	IP67	90-305
150	EUD-150S	105/150/210/350/560	DTA/DVA	IP67	90-305
150	EUM-150S	105/150/210/420	MG/MT	IP66/IP67	90-305
150	IT 0-10 150/100-277/N E A12	0A75	A12 OP	IP20	90-305
150	IT 0-10 150/100-277/N F A12	0A75	A12 OP	IP20	90-305
150	IT 0-10 150/100-277 P67	0A7/1A05/4A2	A12	IP67	90-305
200	EUM-200S	105/150/280/560	MG/MT	IP66/IP67	90-305
200	IT 0-10 200/100-277/N E A12	0A9	A12 OP	IP20	90-305
200	IT 0-10 200/100-277/N F A12	0A9	A12 OP	IP20	90-305
200	IT 0-10 200/100-277 P67	0A7/1A05/1A5/5A6	A12	IP67	90-305
240	ESD-240S	220	DT-R101	IP67	249-528
240	EUD-240S	105/210/420/670	DTA/DVA	IP67	90-305
240	EUM-240S	105/150/350/670	MG/MT	IP66/IP67	90-305
240	IT 0-10 240/100-277/N E A12	1A1	A12 OP	IP20	90-305

功率 (W)	驱动器系列	型号 (×10 = mA)	后缀	IP 等级	输入电压范围 (Vac)
240	IT 0-10 240/100-277/N F A12	1A1	A12 OP	IP20	90-305
240	IT 0-10 240/100-277 P67	0A7/1A05/1A5/6A7	A12	IP67	90-305
320	EUD-320S	220	DT/DV	IP67	90-305
320	EUM-320S	105/150/250/500/760	MG/MT	IP66/IP67	90-305
320	IT 0-10 320/100-277/N E A12	1A6	A12 OP	IP20	90-305
320	IT 0-10 320/100-277/N F A12	1A6	A12 OP	IP20	90-305
320	IT 0-10 320/100-277 P67	1A05/1A5/7A6	A12	IP67	90-305
480	ESD-480S	140/280/420/560/10A	DT/DV	IP67	249-528
480	ESM-480S	140/280/420/560/10A	MG/MT	IP66/IP67	249-528
480	EUD-480S	140/280/420/560/10A	DT/DV	IP67	90-305
600	ESD-600S	170/210/280/420/560/740/980/12A	DT/DV	IP67	249-528
600	EUD-600S	140/170/210/280/420/560/740/980/12A	DT/DV	IP67	90-305
600	EUD-600S	560	DV-C401	IP67	90-305
680	ESM-680S	170/240/350/560/840/15A	MG/MT	IP66/IP67	249-528
680	EUM-680S	170/240/350/560/840/15A	MG/MT	IP66/IP67	90-305
760	SUM-760S	15A	MG/MT	IP66/IP67	90-305
880	ESM-880S	280/420/700/11A/20A	MG/MT	IP66/IP67	249-528
880	ESM-880S	280/420/700/11A/20A	MGS	IP66/IP67	249-528
880	EUM-880S	280/420/700/11A/20A	MG/MT	IP66/IP67	90-305
880	EUM-880S	280/420/700/11A/20A	MGS	IP66/IP67	90-305
1000	SSM-1K0S	400/840/21A	MG/MT	IP66/IP67	249-528
1000	SUM-1K0S	400/840/21A	MG/MT	IP66/IP67	90-305
1200	EBM-1K2S	350/525/740	MG	IP66/IP67	176-305
1200	EFD-1K2S	420/560/740	DT/DV	IP67	180-528
1200	ESM-1K2S	350/525/740	MG/MT	IP66/IP67	249-528
1500	SUM-1K5S	600/12A/31A	MG/MT	IP66/IP67	90-305

注：上表中仅针对具有代表性的产品做了兼容性测试。如有任何问题，敬请联系我司咨询。

20260408